HellermannTyton

596-00858

Article Number: 596-00858

Engravable Metal Solar Placard, PV DC DISCONNECT, 3.75" X 1.0", Aluminum, Black, 5/PK



RoHS

Base Data

Local Order Number	596-00858
Туре	DCDISCTM5ENG
Color	Black (BK)
Features and Benefits	 Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure. Aggressive adhesive ensures strong bond, even on powder coated surfaces. Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability. Optional Paint Shields provide additional protection for pre-printed and variable data placards.
Product Description	Metal Solar Placards offer maximum durability for labeling photovoltaic equipment and components. A special printing process fuses UV stable inks to the placards for long-lasting results, tested to last up to 25 years - even in direct sunlight. Metal Solar Placards are designed to meet or exceed National Electrical Code (NEC) and the requirements of local Authorities Having Jurisdiction (AHJs), that may prefer a placard-style marking over thermal transfer printed labels.
Technical Description	3.75" X 1" Black text on aluminum background that reads as: "PHOTOVOLTAIC DC DISCONNECT." - 10 per pack. Nameplate can be used with standard engraving equipment to add variable data.
Short Description	Engravable Metal Solar Placard, PV DC DISCONNECT, 3.75" X 1.0", Aluminum, Black, 5/PK

Product Dimensions

Length L (Imperial)	3.75 "
Length L (Metric)	92.25 mm
Width W (Imperial)	3.75 "
Width W (Metric)	92.25 mm
Height H (Imperial)	1.0 "
Height H (Metric)	25.4 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	10
Package Quantity (Metric)	5

Material and Specifications

Material	Anodized Aluminum (AA)
Material Shortcut	AA
Adhesive	3M 300LSE Ultra High Bond Permanent Acrylic Adhesive
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	from +50°F (from +10°C)
Halogenfree	Yes
Operating Temperature	-40°F to +203°F (-40°C to +95°C)

ROHS Compliant Yes

UL Recognized (US) Yes

© HellermannTyton 2015