

596-00861

Article Number: 596-00861

Pre-Printed Metal Solar Placard, "MAIN PV AC DISCONNECT", 5.5" X 1.75", Aluminum, Red, 5/PK

**MAIN PHOTOVOLTAIC
SYSTEM
AC DISCONNECT**



Base Data

Local Order Number 596-00861

Type MPVACDISM5

Color Red (RD)

Features and Benefits

- Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.
- Aggressive adhesive ensures strong bond, even on powder coated surfaces.
- Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.
- Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Product Description Metal Solar Placards offer maximum durability for labeling photovoltaic equipment and components. A special printing process fuses UV stable inks to the placards for long-lasting results, tested to last up to 25 years - even in direct sunlight. Metal Solar Placards are designed to meet or exceed National Electrical Code (NEC) and the requirements of local Authorities Having Jurisdiction (AHJs), that may prefer a placard-style marking over thermal transfer printed labels.

Technical Description 5.5" X 3.0" Black text on red background that reads as: "MAIN PV SYSTEM AC DISCONNECT." in 3/8" tall characters. 10 per pkg.

Short Description Pre-Printed Metal Solar Placard, "MAIN PV AC DISCONNECT", 5.5" X 1.75", Aluminum, Red, 5/PK

Product Dimensions

Length L (Imperial) 5.5 "

Length L (Metric) 139.7 mm

Width W (Imperial) 5.5 "

Width W (Metric) 139.7 mm

Height H (Imperial) 1.75 "

Height H (Metric) 44.4 mm

Logistics and Packaging

Quantity Per pieces

Package Quantity 10

Package Quantity (Metric) 5

Material and Specifications

Material Anodized Aluminum (AA)

Material Shortcut AA

Adhesive Shortcut Acrylic

Adhesive 3M 300LSE Ultra High Bond Permanent Acrylic Adhesive

Adhesive Operating Temperature from +50°F (from +10°C)

Halogenfree Yes

Operating Temperature -40°F to +203°F (-40°C to +95°C)

ROHS Compliant Yes

UL Recognized (US) Yes