

## CTM00C2



**Article Number:** 151-30300

**Cable Tie Mount, 0.15" Hole Dia., 0.2" Max Tie Width, PA66, Black, 100/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	CTM00C2
<b>Type</b>	CTM0
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Designed for use with 18 through 50 pound cable ties to provide stability when securing bundles.</li> <li>• Secures with a single screw providing quick installation.</li> </ul>
<b>Product Description</b>	HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.
<b>Short Description</b>	Cable Tie Mount, 0.15" Hole Dia., 0.2" Max Tie Width, PA66, Black, 100/pkg

### Product Dimensions

<b>Length L (Imperial)</b>	0.58 "
<b>Length L (Metric)</b>	14.7 mm
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.37 "
<b>Width W (Metric)</b>	9.4 mm
<b>Cable Tie Width Max. (Imperial)</b>	0.2 "
<b>Cable Tie Width Max. (Metric)</b>	5.0 mm
<b>Height H (Imperial)</b>	0.27 "
<b>Height H (Metric)</b>	6.9 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.15 "
<b>Mounting Hole Diameter D (Metric)</b>	3.8 mm
<b>Mounting Hole Diameter D Max. (Metric)</b>	3.8 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	3.8 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100 Pieces
<b>Carton Quantity</b>	15000

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes