

CTM110M4



Article Number: 151-30406

Cable Tie Mount, 0.19" Hole Dia., 0.2" Max Tie Width, PA66, White, 1000/pkg



Download spec sheet

Base Data

| | |
|------------------------------|---|
| Local Order Number | CTM110M4 |
| Type | CTM1 |
| Color | White (WH) |
| Features and Benefits | <ul style="list-style-type: none"> • Designed for use with 18 through 50 pound cable ties to provide stability when securing bundles. • Secures with a single screw providing quick installation. |
| Product Description | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw. |
| Short Description | Cable Tie Mount, 0.19" Hole Dia., 0.2" Max Tie Width, PA66, White, 1000/pkg |

Product Dimensions

| | |
|---|--------------------------|
| Length L (Imperial) | 0.58 " |
| Length L (Metric) | 14.7 mm |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.37 " |
| Width W (Metric) | 9.4 mm |
| Cable Tie Width Max. (Imperial) | 0.2 " |
| Cable Tie Width Max. (Metric) | 5.0 mm |
| Height H (Imperial) | 0.27 " |
| Height H (Metric) | 6.9 mm |
| Mounting Hole Diameter D (Imperial) | 0.19 " |
| Mounting Hole Diameter D (Metric) | 4.8 mm |
| Mounting Hole Diameter D Max. (Metric) | 4.8 mm |
| Mounting Hole Diameter D Min. (Metric) | 4.8 mm |

Logistics and Packaging

| | |
|----------------------------------|-------|
| Quantity Per | bag |
| Package Quantity (Metric) | 1000 |
| Carton Quantity | 15000 |

Material and Specifications

| | |
|--------------------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL94 V2 |

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL62275

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes