

CTT60R9C2



Article Number: 112-52104

Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Natural, 100/pkg



Download spec sheet

Base Data

Local Order Number	CTT60R9C2
Type	CTT60R
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Head design contains clamping rails to provide full circumferential compression around bundles. • Bent tail allows for quick insertion into head.
Product Description	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	60.0 lbs
Minimum Tensile Strength (Metric)	265.0 N
Length L (Imperial)	8.0 "
Length L (Metric)	205.0 mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19 "
Width W (Metric)	4.7 mm
Bundle Diameter Min. (Imperial)	0.06 "
Bundle Diameter Min. (Metric)	1.5 mm
Bundle Diameter Max. (Imperial)	1.8 "
Bundle Diameter Max. (Metric)	45.0 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100
Carton Quantity	5000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes
Certification/Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes