

DSWS50HSH1

Article Number: 151-06501

Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter .625"-6", Black, POM, PA66HS, 500/Pkg



Download spec sheet

Base Data

Local Order Number	DSWS50HSH1
Type	DSWS5
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • "H" profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle. • Swivels in 360 degree motion to accommodate any area. • Accommodates T50-T250 ties to handle both light duty and heavy duty applications.
Product Description	These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The mounts can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the mounts. The dual swivel saddle spacers accommodate cable ties up to 1/2" wide
Fixation Method (FF)	None
Short Description	Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter .625"-6", Black, POM, PA66HS, 500/Pkg

Product Dimensions

Length L (Imperial)	1.6 "
Length L (Metric)	40.6 mm
Width W (Imperial)	1.0 "
Width W (Metric)	25.4 mm
Height H (Imperial)	0.9 "
Height H (Metric)	23.6 mm
Bundle Diameter Min. (Imperial)	0.7 "
Bundle Diameter Min. (Metric)	16.0 mm
Bundle Diameter Max. (Imperial)	6.0 "
Bundle Diameter Max. (Metric)	152.0 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500
Carton Quantity	500

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2

Minimum Extraction Force (Imperial) 250.0 lbs

Minimum Extraction Force (Metric) 1112 N

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes