

FERM36S

Article Number: 855-49201

Rack Mount Fiber Enclosure-Unloaded, Accepts 6 Adapter Panels for Fiber Counts 36/48, 2U, BK, 1/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number	FERM36S
Type	FERM36S
Color	Black (BK)

- Features and Benefits**
- Removable front and rear covers provide easy access to cables.
 - Slide-out tray with easy-to-grip raised edge.
 - Cable management spools for effective slack management.
 - Optional splice trays to assist with cable splicing.
 - Panel positioning for easier patch cords access.
 - Round edge plastic fiber saddles for easier patch-cord routing.
 - Meet ANSI/TIA/EIA 568-B standards.

Product Description HellermannTyton's rack mount fiber enclosures are the ideal direct termination and splice solution of LAN applications capable of supporting up to 72 fibers. While offering easy-to-use front slide-out trays for effortless access to connections, enclosures are equipped with cable management and cable routing accessories to limit bend radius and add strain relief control. HellermannTyton's Rack Mount Fiber Enclosures easily fit into 19" or 23" racks.

Technical Description HellermannTyton rack mount fiber enclosures provide a secure termination solution for LAN applications and are compatible with standard 19" and 23" equipment racks. Rack mount enclosures accommodate up to 2304 fibers, mount easily and provide easy cable routing access inside the enclosure. Choose from enclosure options to accommodate 3, 6 or 12 standard LGX-style adapter panels.

Short Description Rack Mount Fiber Enclosure-Unloaded, Accepts 6 Adapter Panels for Fiber Counts 36/48, 2U, BK, 1/pkg

Product Dimensions

Length L (Imperial)	12.14 "
Length L (Metric)	308.4 mm
Height in Units	2U
Width W (Imperial)	17.0 "
Width W (Metric)	431.8 mm
Height H (Imperial)	3.5 "
Height H (Metric)	88.9 mm
Depth D (imperial)	12.14 "
Depth D (metric)	308.36 mm

Logistics and Packaging

Quantity Per	box
Package Quantity	1
Package Quantity (Metric)	1
Carton Quantity	1
Weight (imperial)	17

Material and Specifications

© HellemannTyton 2015