

FEWM12



Article Number: 855-04207

Wall Mount Fiber Enclosure - Unloaded, accepts 2 Adapter Panels, 1 Splice Tray, Black, 1/pkg



[Download spec sheet](#)

Base Data

Local Order Number FEWM12

Type FEWM12

Color Black (BK)

- Features and Benefits**
- Durable stainless steel construction for long life.
 - Cable management spools for effective slack management.
 - Bend radius control to minimize hand and wrist strain.
 - Smooth grommet entry to protect cables from damage.
 - Locking tab for added security.
 - Meet ANSI/TIA/EIA 568-B standards.

Product Description To effectively manage optical fiber terminations and splices, HellermannTyton offers a line of wall mount enclosures. They provide a termination solution for LAN applications requiring fully enclosed wall mount enclosures. This product is designed to support up to two modular adapter panels, providing the flexibility to have 12 or 16 fibers when fully loaded. This enclosure houses one splice tray.

Technical Description HellermannTyton wall mount fiber enclosures provide a secure termination solution for LAN applications requiring fully enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4 standard LGX-style adapter panels.

Short Description Wall Mount Fiber Enclosure - Unloaded, accepts 2 Adapter Panels, 1 Splice Tray, Black, 1/pkg

Product Dimensions

Length L (Imperial) 2.1 "

Length L (Metric) 53.3 mm

Width W (Imperial) 13.0 "

Width W (Metric) 330.2 mm

Height H (Imperial) 15.63 "

Height H (Metric) 397.0 mm

Depth D (metric) 93.98 mm

Depth D (imperial) 3.7 "

Logistics and Packaging

Quantity Per box

Package Quantity 1

Package Quantity (Metric) 1

Carton Quantity 1

Material and Specifications

Material Metal

