# HellermannTyton

## FEWM6

1	Article Number: 904-00717 Wall Mount Fiber Enclosure - Unloaded, accepts 1 Adapter Panel, Black, 1/pkg
	bad spec sheet
Base Data	
Local Order Numb	er FEWM6
Тур	De FEWM6
Col	or Black (BK)

- Features and Benefits Durable stainless steel construction for long life.
  - Cable management spools for effective slack management.
    - Bend radius control to minimize hand and wrist strain.
  - Smooth grommet entry to protect cables from damage.
  - Locking tab for added security.
  - Meet ANSI/TIA/EIA 568-B standards.
- Product DescriptionHellermannTyton wall mount fiber enclosures provide a secure termination solution for applications requiring fully<br/>enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and<br/>provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4<br/>standard LGX adapter panels.Technical DescriptionHellermannTyton wall mount fiber enclosures provide a secure termination solution for LAN applications requiring fully
- enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4 standard LGX-style adapter panels.

Short Description Wall Mount Fiber Enclosure - Unloaded, accepts 1 Adapter Panel, Black, 1/pkg

### **Product Dimensions**

Length L (Imperial)	1.5 "
Length L (Metric)	38.1 mm
Width W (Imperial)	6.5 "
Width W (Metric)	165.1 mm
Height H (Imperial)	7.0 "
Height H (Metric)	177.8 mm

### Logistics and Packaging

Quantity Per box

Package Quantity (Metric) 1

#### **Material and Specifications**

Material Metal