# HellermannTyton

## HDM3120HIRC2

Article Number: 151-00439

Standard Torque Mount, Mounting Hole .3125", Max Torque 115.0 lb - in, PA66HIRHSUV, Black, 100/pkg

RoHS



#### **Base Data**

Local Order Number HDM3120HIRC2

Type HDM312

Color Black (BK)

Features and Benefits • Mount and tie combination makes it easy to service bundles in the field.

• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.

• Eliminates the needs for multiple sized fix diameter clamps.

Product Description This mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps;

which reduces inventory and purchasing costs while simplifying the assembly process.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Standard Torque Mount, Mounting Hole .3125", Max Torque 115.0 lb - in, PA66HIRHSUV, Black, 100/pkg

### **Product Dimensions**

Length L (Imperial) 1.4 "

Length L (Metric) 36.3 mm

Width W (Imperial) 0.8 "

Width W (Metric) 19.3 mm

Cable Tie Width Max. (Imperial) 0.5

Cable Tie Width Max. (Metric) 12.7 mm

Width W2 (Imperial) 0.5 "

Width W2 (Metric) 13.3 mm

Height H (Imperial) 0.7 "

Height H (Metric) 16.7 mm

Height H2 (Imperial) 0.3 "

Height H2 (Metric) 8.0 mm

Mounting Hole Diameter D (Imperial) 0.3 "

Mounting Hole Diameter D (Metric) 7.8 mm

# **Logistics and Packaging**

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 3000 Pieces

#### **Material and Specifications**

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Maximum Torque (kgf-cm) 132.5 kgf-cm

Maximum Torque (lbf-ft) 9.583 lbf-ft

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes