

HDM500BHIHSUVH4

Article Number: 151-07400

High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number HDM500BHIHSUVH4

Type HDM500

Color Black (BK)

Features and Benefits

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

Product Description This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

Fixation Method (FF) Screw Mounting and Rivet

Short Description High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.9 "

Length L (Metric) 47.0 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.5 "

Mounting Hole Diameter D (Metric) 12.95 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 500

Weight (Metric) 1 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Maximum Torque (kgf-cm) 1576 kgf-cm

Maximum Torque (lbf-ft) 114 lbf-ft

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes

© HellemannTyton 2015