

HDM501HIHSUVH4



Article Number: 151-07500

Medium Torque Mount, Mounting Hole 0.5", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg



Download spec sheet

Base Data

Local Order Number HDM501HIHSUVH4

Type HDM501

Color Black (BK)

Features and Benefits The heavy duty mounts are designed for use with HellermannTyton's heavy duty T250, T255 and wide strap cable ties to harness wires and hoses; however, they accept all standard cable ties up to .5" wide.

These mounts contain a small tab inside the mounting hole to temporarily engage the threads, which allows assemblers to pre-install the mount on a stud before securing with a washer and a nut.

The arched "H" profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters.

The mounts are available in standard, medium and high torque versions. The high torque version is designed for use with power-assisted impact wrenches and is molded with a metal bushing to withstand the forces required to tighten grade 8 bolts.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Medium Torque Mount, Mounting Hole 0.5", Max Torque 40.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.8 "

Length L (Metric) 46.0 mm

Width W (Imperial) 1.0 "

Width W (Metric) 24.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.5 "

Mounting Hole Diameter D (Metric) 12.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 500

Weight (Metric) 1 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHSUV
Flammability UL94 V2
Maximum Torque (lbf-ft) 40 lbf-ft
Maximum Torque (kgf-cm) 553 kgf-cm
Operating Temperature -40°F to +230°F (-40°C to +110°C)
ROHS compliant (Article 4 - 1) Yes