

## IMP1.7510C2

Article Number: 151-00236

IMP Plate, 1.75" X .75", Nylon, White, 100/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number IMP1.7510C2

Type IMP1.75

Color White (WH)

**Features and Benefits**

- Identification Marker Plates can be marked with a permanent pen, printed labels or hot stamped for a wide variety of labeling options.
- Any size bundle diameter can be marked because it is only dependent upon the length of the cable tie selected, provided the cable tie width does not exceed .29".
- The marker plates are stamped from nylon, making them a durable and long term method of identification. The mounting holes allow the marker to be mounted as a flag, tag or wrapped around the cable or bundle for a wide variety of installed positions.

**Product Description** Identification Marker Plates can be mounted in any direction, either vertically or horizontally as flags, tags or wraparound identification plates. They can be marked with HellermannTyton marking pens (T82-R or T82-S), thermal transfer or laser labels or hot stamped. The markers are manufactured from nylon and are white in color.

Mounting method Identification ETIM Others

Short Description IMP Plate, 1.75" X .75", Nylon, White, 100/pkg

### Product Dimensions

Length L (Imperial) 1.75 "

Length L (Metric) 44.4 mm

Length L2 (Imperial) 1.23 "

Length L2 (Metric) 32.5 mm

Identification Plate Position attached to bundle

Variant Other

Width W (Imperial) 0.75 "

Width W (Metric) 19.05 mm

Cable Tie Width Max. (Imperial) 0.2 "

Cable Tie Width Max. (Metric) 4.60 mm

Thickness T (Imperial) 0.016 "

Thickness T (Metric) 0.4

Width of Printable Area (imperial) 1.28 "

Width of printable area (metric) 26.20 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity 100

**Package Quantity (Metric)** 100

**Carton Quantity** 100

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes