

## IMP2.5W1.7510C2



**Article Number:** 151-42269

**IMP Plate, 2.5" X 1.75", Nylon, White, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** IMP2.5W1.7510C2

**Type** IMP2.5

**Color** White (WH)

**Features and Benefits**

- Identification Marker Plates can be marked with a permanent pen, printed labels or hot stamped for a wide variety of labeling options.
- Any size bundle diameter can be marked because it is only dependent upon the length of the cable tie selected, provided the cable tie width does not exceed .29".
- The marker plates are stamped from nylon, making them a durable and long term method of identification. The mounting holes allow the marker to be mounted as a flag, tag or wrapped around the cable or bundle for a wide variety of installed positions.

**Product Description** Identification Marker Plates can be mounted in any direction, either vertically or horizontally as flags, tags or wraparound identification plates. They can be marked with HellermannTyton marking pens (T82-R or T82-S), thermal transfer or laser labels or hot stamped. The markers are manufactured from nylon and are white in color.

**Mounting method Identification ETIM** Others

**Short Description** IMP Plate, 2.5" X 1.75", Nylon, White, 100/pkg

### Product Dimensions

**Length L (Imperial)** 2.5 "

**Length L (Metric)** 63.5 mm

**Length L2 (Imperial)** 2.03 "

**Length L2 (Metric)** 51.56 mm

**Identification Plate Position** attached to bundle

**Variant** Other

**Width W (Imperial)** 1.75 "

**Width W (Metric)** 44.4 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.80 mm

**Thickness T (Imperial)** 0.016 "

**Thickness T (Metric)** 0.4

**Width of Printable Area (imperial)** 2.03 "

**Width of printable area (metric)** 51.60 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity** 100

**Package Quantity (Metric)** 100 Pieces

**Carton Quantity** 100 Pieces

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes