# HellermannTyton

### IMP3.510C2

Article Number: 151-42359

IMP Plate, 3.5" X .75", Nylon, White, 100/pkg







#### **Base Data**

Local Order Number IMP3.510C2

Type IMP3.5

Color White (WH)

Features and Benefits · Identification Marker Plates can be marked with a permanent pen, printed labels or hot stamped for a wide variety of

labeling options.

· Any size bundle diameter can be marked because it is only dependent upon the length of the cable tie selected,

provided the cable tie width does not exceed .29".

• The marker plates are stamped from nylon, making them a durable and long term method of identification. The mounting holes allow the marker to be mounted as a flag, tag or wrapped around the cable or bundle for a wide

variety of installed positions.

Product Description

Identification Marker Plates can be mounted in any direction, either vertically or horizontally as flags, tags or wraparound identification plates. They can be marked with HellermannTyton marking pens (T82-R or T82-S), thermal

transfer or laser labels or hot stamped. The markers are manufactured from nylon and are white in color.

Mounting method Identification ETIM Others

Short Description

IMP Plate, 3.5" X.75", Nylon, White, 100/pkg

#### **Product Dimensions**

Length L (Imperial) 3.5 "

Length L (Metric) 88.9 mm

Length L2 (Imperial) 3.02 "

Length L2 (Metric) 76.9 mm

Identification Plate Position attached to bundle

Variant Other

Width W (Imperial) 0.75 "

Width W (Metric) 19.05 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.80 mm

Thickness T (Imperial) 0.016 "

Thickness T (Metric) 0.4

Width of printable area (metric) 77.00 mm

Width of Printable Area (imperial) 3.03 "

## **Logistics and Packaging**

Quantity Per bag

Package Quantity 100

Package Quantity (Metric) 100 Pieces

Carton Quantity 100 Pieces

# **Material and Specifications**

Material Polyamide 6.6 (PA66)

Material Shortcut PA66
Flammability UL94 V2

Halogenfree Yes

**Operating Temperature**  $-40^{\circ}\text{F to } +185^{\circ}\text{F } (-40^{\circ}\text{C to } +85^{\circ}\text{C})$ 

ROHS Compliant Yes