

IT50RD9K2



Article Number: 111-85219

Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Natural, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number IT50RD9K2

Type IT50RD

Color Natural (NA)

- Features and Benefits**
- Identification plate feature allows bundles to be easily marked and identified.
 - Wire and cable harnesses can be secured and identified using just one product, which saves time.
 - Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.

Product Description HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.

Mounting method Identification ETIM Others

Short Description Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Natural, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 8.0 "

Length L (Metric) 205.0 mm

Fixation Method None

Identification Plate Position attached to bundle

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 1.1 "

Width W (Metric) 29.0 mm

Width W2 (Imperial) 0.19 "

Width W2 (Metric) 4.7 mm

Height H (Imperial) 1.04 "

Height H (Metric) 26.3 mm

Bundle Diameter Min. (Imperial) 0.4 "

Bundle Diameter Min. (Metric) 10.0 mm

Bundle Diameter Max. (Imperial) 1.7 "

Bundle Diameter Max. (Metric) 44.0 mm

Outside Diameter Min. (Imperial) 0.393 "

Outside Diameter Min. (Metric) 10.00 mm

Outside Diameter Max. (Imperial) 1.73 "

Outside Diameter Max. (Metric) 44.00 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.2

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 1000

Weight (Metric) 2 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

US MILSPEC MS3368-3-9C

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL-ZODZ2.E64139

Cage Code 53421

MS3368

SAE AS33681

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes