

LKCRF19C2



Article Number: 151-27000

Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 100/pk



Download drawing



Download spec sheet

Base Data

Local Order Number LKCRF19C2

Type LKCRF1

Color Natural (NA)

Features and Benefits The low profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole. This mount is ideal for use in applications where space is limited.

Short Description Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 100/pk

Product Dimensions

Length L (Imperial) 0.938 "

Length L (Metric) 24.0 mm

Fixation Method with Rivet (Mounts)

Width W (Imperial) 0.47 "

Width W (Metric) 12.0 mm

Height H (Imperial) 0.157 "

Height H (Metric) 3.99 mm

Panel Thickness Max. (Imperial) 0.134 "

Panel Thickness Max. (Metric) 3.40 mm

Mounting Hole Diameter D (Imperial) 0.25 "

Mounting Hole Diameter D (Metric) 6.4 mm

Mounting Hole Diameter D Max. (Imperial) 0.255 "

(Imperial)

Mounting Hole Diameter D Max. (Metric) 6.5 mm

(Metric)

Mounting Hole Diameter D Min. (Metric) 6.4 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 4000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

© HellemannTyton 2015