

## LKCRF19H4



**Article Number:** 151-27009

**Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 500/pk**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** LKCRF19H4

**Type** LKCRF1

**Color** Natural (NA)

**Features and Benefits** The low profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole. This mount is ideal for use in applications where space is limited.

**Short Description** Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 500/pk

### Product Dimensions

**Length L (Imperial)** 0.938 "

**Length L (Metric)** 24.0 mm

**Fixation Method** with Rivet (Mounts)

**Width W (Imperial)** 0.47 "

**Width W (Metric)** 12.0 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.8 mm

**Height H (Imperial)** 0.157 "

**Height H (Metric)** 4.0 mm

**Panel Thickness Max. (Imperial)** 0.134 "

**Panel Thickness Max. (Metric)** 3.40 mm

**Mounting Hole Diameter D (Imperial)** 0.25 "

**Mounting Hole Diameter D (Metric)** 6.4 mm

**Mounting Hole Diameter D Max. (Metric)** 6.4 mm

**Mounting Hole Diameter D Min. (Metric)** 6.4 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500 Pieces

**Carton Quantity** 4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

---

© HellemannTyton 2015