

LTM2500C2

Article Number: 151-00358

Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number LTM2500C2

Type LTM250

Color Black (BK)

Features and Benefits • The strap is parallel to the mount when inserted into the head, providing a mounting point for where the cable ties.

Product Description The Lashing Tie Mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.

Short Description Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg

Product Dimensions

Length L (Imperial) 1.5 "

Length L (Metric) 37.1 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 0.73 "

Width W (Metric) 18.5 mm

Cable Tie Width Max. (Imperial) 0.49 "

Cable Tie Width Max. (Metric) 12.5 mm

Height H (Imperial) 0.38 "

Height H (Metric) 9.6 mm

Mounting Hole Diameter D (Imperial) 0.26 "

Mounting Hole Diameter D (Metric) 6.6 mm

Mounting Hole Diameter D Max. 6.6 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 6.6 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 3000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

© HellemannTyton 2015