

MB2.510M4



Article Number: 151-28902

Screw Fastened Bases, .1" Max tie width, .11" Hole Dia., .625" Length/Width, PA66, White, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number MB2.510M4

Type MB2.5

Color White (WH)

- Features and Benefits**
- For use with 18 pound cable ties to provide stability when securing bundles.
 - Secures with two or four screws, providing multiple use options.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton screw fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description Screw Fastened Bases, .1" Max tie width, .11" Hole Dia., .625" Length/Width, PA66, White, 1000/pkg

Product Dimensions

Length L (Imperial) 0.625 "

Length L (Metric) 15.9 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 0.625 "

Width W (Metric) 15.9 mm

Cable Tie Width Max. (Imperial) 0.1 "

Cable Tie Width Max. (Metric) 2.54 mm

Height H (Imperial) 0.13 "

Height H (Metric) 3.3 mm

Mounting Hole Diameter D (Imperial) 0.11 "

Mounting Hole Diameter D (Metric) 2.8 mm

Mounting Hole Diameter D Max. 2.8 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 2.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 15000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes