

MB29M4



Article Number: 151-00297

Cable Tie Mount, 0.193" Hole Dia., 0.18" Max Tie Width, PA66, Natural, 1000/pkg



Download spec sheet

Base Data

Local Order Number MB29M4

Type MB2

Color Natural (NA)

Features and Benefits

- For use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Low profile design offers use in space constrained areas.
- Secures with a single screw providing quick installation.

Product Description HellermannTyton cable tie screw mounts are used with 18 through 50 pound cable ties to provide stability when securing bundles. The low profile design allows for use in space constrained areas. The mounts are installed quick and easy by securing a single screw.

Short Description Cable Tie Mount, 0.193" Hole Dia., 0.18" Max Tie Width, PA66, Natural, 1000/pkg

Product Dimensions

Length L (Imperial) 0.81 "

Length L (Metric) 20.6 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 0.49 "

Width W (Metric) 12.5 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.6 mm

Height H (Imperial) 0.13 "

Height H (Metric) 3.3 mm

Height H2 (Imperial) 0.05 "

Height H2 (Metric) 1.7 mm

Mounting Hole Diameter D (Imperial) 0.193 "

Mounting Hole Diameter D (Metric) 4.9 mm

Mounting Hole Diameter D Max. 4.9 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 4.9 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 20000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes
UL Listed (US and Canada) No
UL Recognized (US and Canada) No