

## MB40C2

Article Number: 151-00320

Screw Fastened Bases, .18" Max tie width, .18" Hole Dia., 1.12" Length/Width, PA66, Black, 100/pkg



Download spec sheet

### Base Data

Local Order Number MB40C2

Type MB4

Color Black (BK)

- Features and Benefits**
- For use with 18 through 50 pound cable ties to provide stability when securing bundles.
  - Secures with two or four screws; providing multiple options.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton screw fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Screw Fastened Bases, .18" Max tie width, .18" Hole Dia., 1.12" Length/Width, PA66, Black, 100/pkg

### Product Dimensions

Length L (Imperial) 1.12 "

Length L (Metric) 28.5 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 1.12 "

Width W (Metric) 28.5 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.6 mm

Height H (Imperial) 0.19 "

Height H (Metric) 4.8 mm

Mounting Hole Diameter D (Imperial) 0.18 "

Mounting Hole Diameter D (Metric) 4.6 mm

Mounting Hole Centers (Imperial) 0.8 "

Mounting Hole Diameter D Max. (Metric) 4.6 mm

Mounting Hole Diameter D Min. (Metric) 4.6 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 5000

### Material and Specifications

Material Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes