

## MB4A10A2H4



Article Number: 151-00322

Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 500/pkg



Download spec sheet

### Base Data

<b>Local Order Number</b>	MB4A10A2H4
<b>Type</b>	MB4A
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• For use with 18 and 30 pound cable ties to provide stability when securing bundles.</li> <li>• Secures with rubber based adhesive backing and/or two or four screws.</li> <li>• 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.</li> </ul>
<b>Product Description</b>	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
<b>Short Description</b>	Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 500/pkg

### Product Dimensions

<b>Length L (Imperial)</b>	1.12 "
<b>Length L (Metric)</b>	28.5 mm
<b>Fixation Method</b>	Screw Mounting and Adhesive
<b>Width W (Imperial)</b>	1.12 "
<b>Width W (Metric)</b>	28.5 mm
<b>Cable Tie Width Max. (Imperial)</b>	0.18 "
<b>Cable Tie Width Max. (Metric)</b>	4.6 mm
<b>Height H (Imperial)</b>	0.23 "
<b>Height H (Metric)</b>	5.8 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.18 "
<b>Mounting Hole Diameter D (Metric)</b>	4.6 mm
<b>Mounting Hole Centers (Imperial)</b>	0.8 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	4.6 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	4.6 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500
<b>Carton Quantity</b>	4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Acrylate with base of acrylic foam

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes