

## MB5A0F4

Article Number: 151-28605

Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, Black, 250/pkg



Download drawing



Download spec sheet

### Base Data

**Local Order Number** MB5A0F4

**Type** MB5A

**Color** Black (BK)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, Black, 250/pkg

### Product Dimensions

**Length L (Imperial)** 1.49 "

**Length L (Metric)** 37.7 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.49 "

**Width W (Metric)** 37.7 mm

**Cable Tie Width Max. (Imperial)** 0.35 "

**Cable Tie Width Max. (Metric)** 8.9 mm

**Height H (Imperial)** 0.28 "

**Height H (Metric)** 7.1 mm

**Mounting Hole Diameter D (Imperial)** 0.19 "

**Mounting Hole Diameter D (Metric)** 4.8 mm

**Mounting Hole Centers (Imperial)** 1.0 "

**Thickness of Adhesive TA (Imperial)** 0.031 "

**Mounting Hole Diameter D Max. (Metric)** 4.8 mm

**Mounting Hole Diameter D Min. (Metric)** 4.8 mm

**Thickness of Adhesive TA (Metric)** 0.8 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 250

**Carton Quantity** 2000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Adhesive Shortcut</b>	Synthetic rubber T50
<b>Adhesive Operating Temperature</b>	-4°F to +122°F (-20°C to +50°C)
<b>Flammability</b>	UL94 V2 (excluding adhesive)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes