

MB5A10C2

Article Number: 151-28529

Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 100/pkg



Download spec sheet

Base Data

Local Order Number MB5A10C2

Type MB5A

Color White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
 - Secures with rubber based adhesive backing and/or two or four screws.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 100/pkg

Product Dimensions

Length L (Imperial) 1.49 "

Length L (Metric) 37.7 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 1.49 "

Width W (Metric) 37.7 mm

Cable Tie Width Max. (Imperial) 0.35 "

Cable Tie Width Max. (Metric) 8.9 mm

Height H (Imperial) 0.28 "

Height H (Metric) 7.1 mm

Mounting Hole Diameter D (Imperial) 0.19 "

Mounting Hole Diameter D (Metric) 4.8 mm

Mounting Hole Centers (Imperial) 1.0 "

Thickness of Adhesive TA (Imperial) 0.031 "

Mounting Hole Diameter D Max. 4.8 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 4.8 mm

Thickness of Adhesive TA (Metric) 0.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 1000 Pieces

Weight (Metric) 1.8 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Synthetic rubber with base of polyethylene foam
Adhesive Shortcut	Synthetic rubber T50
Adhesive Operating Temperature	-4°F to +122°F (-20°C to +50°C)
Flammability	UL94 V2 (excluding adhesive)
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes