

## MMB.50M4



**Article Number:** 151-30001

**Masonry Mount, 1.24" Length, .25" Hole Dia., .18" Max. Cable Tie Width, PA46, Black, 1000/pkg**



Download spec sheet

### Base Data

**Local Order Number** MMB.50M4

**Type** MMB.5

**Color** Black (BK)

**Features and Benefits**

- Masonry Mounts provides a permanent solution when fastening wire and cables to masonry surfaces.
- The mounts have easy installation into predrilled holes allowing for faster use.

**Product Description** HellermannTyton masonry mounts provide a permanent mounting solution when fastening wire and cables to masonry surfaces. Designed for easy installation by simply tapping into predrilled holes.

**Short Description** Masonry Mount, 1.24" Length, .25" Hole Dia., .18" Max. Cable Tie Width, PA46, Black, 1000/pkg

### Product Dimensions

**Length L (Imperial)** 1.24 "

**Length L (Metric)** 31.5 mm

**Fixation Method** with Fir Tree (Mounts)

**Width W (Imperial)** 0.375 "

**Width W (Metric)** 9.5 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.22 "

**Width W2 (Metric)** 5.6 mm

**Width W3 (Imperial)** 0.308 "

**Width W3 (Metric)** 7.8 mm

**Height H (Imperial)** 0.37 "

**Height H (Metric)** 9.4 mm

**Mounting Hole Diameter D (Imperial)** 0.25 "

**Mounting Hole Diameter D (Metric)** 6.35 mm

**Mounting Hole Diameter D Max.** 6.35 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 6.35 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 1000

**Carton Quantity** 9000

### Material and Specifications

---

**Material** Polyamide 4.6 (PA46)  
**Material Shortcut** PA46  
**Flammability** UL94 V2  
**Operating Temperature** -40°F to +275°F (-40°C to +135°C)  
**ROHS Compliant** Yes