

MSBT1200HIRHSH1

Article Number: 151-29301

Saddle Mount For Button Head Tie, Mounting Hole Diameter 0.44" - 0.82", PA66HIRHSUV, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number MSBT1200HIRHSH1

Type MSBT120

Color Black (BK)

- Features and Benefits**
- Secures up to three bundles for multiple routing.
 - Provides parallel spacing between frame rail and adjacent bundles to reduce wear.
 - Manufactured with a pilot bushing which prevent the cable tie from chafing against the burr edge of the mounting hole.

Product Description HellermannTyton's saddle mounts are designed to be used with HellermannTyton's button head ties, and stand off bundles from frame rails, providing clearance from bolts and other protrusions for protection against abrasion. This also allows the flow-through of salt, dirt, and other impurities from the road which prevent unwanted build-up on hoses and harnesses.

Short Description Saddle Mount For Button Head Tie, Mounting Hole Diameter 0.44" - 0.82", PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.9 "

Length L (Metric) 48.3 mm

Bundle Diameter 2nd Loop Max. (Imperial) 1.0 "

Width W (Imperial) 0.65 "

Width W (Metric) 16.5 mm

Height H (Imperial) 0.8 "

Height H (Metric) 20.6 mm

Height H2 (Imperial) 0.9 "

Height H2 (Metric) 22.2 mm

Mounting Hole Diameter D Min. (Imperial) 0.44 "

Mounting Hole Diameter D Max. (Imperial) 0.82 "

Bundle Diameter 1st Loop Max. (Imperial) 6.0 "

152.4 mm

Bundle Diameter 1st Loop Max. (Metric)

Mounting Hole Diameter D Max. (Metric) 20.8 mm

Mounting Hole Diameter D Min. (Metric) 11.2 mm

Bundle Diameter 2nd Loop Max. (Metric) 25.4 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-65°F to +230°F (-54°C to +110°C)
ROHS compliant (Article 4 - 1)	Yes