

PR1M4



Article Number: 181-00139

Panel Rivet, PA66, Natural, 1,000/bag



Download drawing



Download spec sheet

Base Data

Local Order Number PR1M4

Type PR1

Color Natural (NA)

Features and Benefits

- Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity.
- Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool.
- Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.

Product Description HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

Short Description Panel Rivet, PA66, Natural, 1,000/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 107.0 lbs

Minimum Tensile Strength (Metric) 478 N

Panel Thickness Max. (Imperial) 0.28 "

Panel Thickness Max. (Metric) 7.0 mm

Panel Thickness Min. (Imperial) 0.15 "

Panel Thickness Min. (Metric) 3.9 mm

Mounting Hole Diameter D (Imperial) 0.2 "

Mounting Hole Diameter D (Metric) 5.0 mm

Diameter Max. (Imperial) 0.02 "

Diameter Max. (Metric) 0.51 mm

Mounting Hole Diameter D Max. (Metric) 5.0 mm

Mounting Hole Diameter D Min. (Metric) 5.0 mm

Logistics and Packaging

Quantity Per EA

Package Quantity 1000.0

Package Quantity (Metric) 1000.0

Carton Quantity 1000.0

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2
Operating Temperature -40°F to +176°F (-40°C to +80°C)
ROHS Compliant Yes
Certification/Specification IMQ