

RT255S0HIRX2



Article Number: 115-01200

Releasable Cable Tie, 8.9" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Download spec sheet

Base Data

Local Order Number	RT255S0HIRX2
Type	RT255S
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Special design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use.
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, 8.9" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	250.0 lbs
Minimum Tensile Strength (Metric)	1115.0 N
Length L (Imperial)	8.9 "
Length L (Metric)	225.0 mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	Yes
Width W (Imperial)	0.5 "
Width W (Metric)	12.6 mm
Bundle Diameter Min. (Imperial)	0.49 "
Bundle Diameter Min. (Metric)	12.5 mm
Bundle Diameter Max. (Imperial)	2.2 "
Bundle Diameter Max. (Metric)	55.0 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	25
Carton Quantity	1000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes