

## S2CM258HIRHSH1

Article Number: 151-29400

Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg



Download spec sheet

### Base Data

**Local Order Number** S2CM258HIRHSH1

**Type** S2CM25

**Color** Gray (GY)

**Features and Benefits**

- Two way saddle separates bundles from wear and chafing.
- Socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt.
- Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.

**Product Description** HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc...) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, this "H" profile on the saddle mount provides a tight circumferential loop on large and small bundles.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

### Product Dimensions

**Length L (Imperial)** 1.8 "

**Length L (Metric)** 45.0 mm

**Width W (Imperial)** 1.2 "

**Width W (Metric)** 30.0 mm

**Cable Tie Width Max. (Imperial)** 0.5 "

**Cable Tie Width Max. (Metric)** 12.5 mm

**Height H (Imperial)** 0.9 "

**Height H (Metric)** 23.0 mm

**Height H2 (Imperial)** 0.6 "

**Height H2 (Metric)** 15.0 mm

**Bundle Diameter Max. (Imperial)** 3.5 "

**Bundle Diameter Max. (Metric)** 89.0 mm

**Mounting Hole Diameter D (Imperial)** 0.24 "

**Mounting Hole Diameter D (Metric)** 6.0 mm

**Stud Size (Imperial)** 0.25 "

**Stud Size (Metric)** 6.35 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500 Pieces

**Carton Quantity** 500

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes