

## SAM83HIRHSH1



**Article Number:** 151-29600

**Axial Oval Mount, Bolt Hole Diameter .31", PA66HIRHS, Gray, 500/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	SAM83HIRHSH1
<b>Type</b>	SAM83
<b>Color</b>	Gray (GY)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Positions bundles off cross members and frame rails to prevent abrasion and chafing.</li> <li>• Metal insert bushing accommodates high torque installation.</li> <li>• Made with high impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.</li> </ul>
<b>Product Description</b>	HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.
<b>Fixation Method (FF)</b>	Screw Mounting and Rivet
<b>Short Description</b>	Axial Oval Mount, Bolt Hole Diameter .31", PA66HIRHS, Gray, 500/pkg

### Product Dimensions

<b>Length L (Imperial)</b>	1.4 "
<b>Length L (Metric)</b>	34.0 mm
<b>Width W (Imperial)</b>	1.0 "
<b>Width W (Metric)</b>	26.0 mm
<b>Height H (Imperial)</b>	1.4 "
<b>Height H (Metric)</b>	35.0 mm
<b>Stud Size (Imperial)</b>	0.3125 "
<b>Stud Size (Metric)</b>	8.0 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500 Pieces
<b>Carton Quantity</b>	500

### Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes

