

## SM1BK75MT



Article Number: 800-00004

Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/RL



Download spec sheet

### Base Data

<b>Local Order Number</b>	SM1BK75MT
<b>Type</b>	SM1
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Fits in holes of all shapes and sizes without the aid of tools or adhesives, making installation easy.</li> <li>• Easily cut to the right length with scissors, thus reducing stock and eliminating waste.</li> <li>• Can be used on any type of material including wood, steel, aluminum, plexiglass and glass, ensuring flexibility of application.</li> </ul>
<b>Product Description</b>	EdgeGuard is used to cover panel edging to protect cables, prevent chafing and provide an attractive finish. The EdgeGuard is manufactured from a flexible PVC compound ensuring ease of use.
<b>Short Description</b>	Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/RL

### Product Dimensions

<b>Length L (Imperial)</b>	246.1 ft
<b>Length L (Metric)</b>	75 m
<b>Reel Length (imperial)</b>	246.1 ft
<b>Width W (Imperial)</b>	0.1969 "
<b>Width W (Metric)</b>	5.0 mm
<b>Width W2 (Imperial)</b>	0.039 "
<b>Width W2 (Metric)</b>	1.0 mm
<b>Width W3 (Imperial)</b>	0.07 "
<b>Width W3 (Metric)</b>	1.8 mm
<b>Width W4 (imperial)</b>	0.165 "
<b>Width W4 (metric)</b>	4.2 mm
<b>Height H (Imperial)</b>	0.248 "
<b>Height H (Metric)</b>	6.3 mm
<b>Height H2 (Imperial)</b>	0.193 "
<b>Height H2 (Metric)</b>	4.9 mm
<b>Panel Thickness Max. (Imperial)</b>	0.079 "
<b>Panel Thickness Max. (Metric)</b>	2.00 mm
<b>Panel Thickness Min. (Imperial)</b>	0.039 "
<b>Panel Thickness Min. (Metric)</b>	1.00 mm

### Logistics and Packaging

Quantity Per reel

**Package Quantity** 246.1 ft  
**Package Quantity (Metric)** 75 m  
**Carton Quantity** 75 Meter  
**Weight (Metric)** 2.56 kg

---

## Material and Specifications

**Material** Polyvinylchloride (PVC)  
**Material Shortcut** PVC  
**Flammability** UL94 HB  
**Operating Temperature** -85°F to +221°F (-65°C to +105°C)  
**ROHS Compliant** Yes