

T120MR9K2



Article Number: 113-12029

Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number	T120MR9K2
Type	T120MR
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Part design applies easily to any #1/4" Screw • Stud style provides low insertion and high extraction force.
Product Description	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
Short Description	Screw Mount Tie, 18lb, 4.3" Long, Max Bun Diameter 4.02", #1/4 Screw, PA66, Natural, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	120.0 lbs
Minimum Tensile Strength (Metric)	535 N
Length L (Imperial)	15.6 "
Length L (Metric)	395.0 mm
Fixation Method	fixing hole
Identification Plate Position	none
Mounting Screw Type	M6
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3 "
Width W (Metric)	7.6 mm
Height H (Imperial)	0.31 "
Height H (Metric)	7.9 mm
Bundle Diameter Min. (Imperial)	0.2 "
Bundle Diameter Min. (Metric)	5.0 mm
Bundle Diameter Max. (Imperial)	4.0 "
Bundle Diameter Max. (Metric)	102.0 mm
Mounting Hole Diameter D (Imperial)	0.26 "
Mounting Hole Diameter D (Metric)	6.5 mm
Thickness T (Imperial)	0.07 "
Cable Tie Head Length (Imperial)	1.12 "
Cable Tie Head Width (Imperial)	0.51 "
Mounting Hole Diameter D Max.	6.5 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 6.5 mm

Thickness T (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50 Pieces

Weight (Metric) 5.8 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Recognized (US and Canada) Yes