

## T120R0PPH4



**Article Number:** 111-12066

**Heavy Duty Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg**



Download spec sheet

### Base Data

**Local Order Number** T120R0PPH4

**Type** T120R

**Color** Black (BK)

**Features and Benefits**

- Polypropylene cable ties provide excellent resistance to chemicals and salts.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 60.0 lbs

**Minimum Tensile Strength (Metric)** 267.0 N

**Length L (Imperial)** 15.35 "

**Length L (Metric)** 390.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Bundle Diameter Min. (Imperial)** 0.5 "

**Bundle Diameter Min. (Metric)** 12.7 mm

**Bundle Diameter Max. (Imperial)** 4.1 "

**Bundle Diameter Max. (Metric)** 105.0 mm

**Thickness T (Imperial)** 0.07 "

**Thickness T (Metric)** 1.8 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500 Pieces

**Carton Quantity** 1000 Pieces

**Weight (Metric)** 5.2 kg

## Material and Specifications

---

**Material** Polypropylene (PP)

**Material Shortcut** PP

**Flammability** UL94 HB

**Halogenfree** Yes

**Operating Temperature** -40°F to +239°F (-40°C to +115°C)

**ROHS Compliant** Yes