

## T18L0HSC2



**Article Number:** 111-00403

**High Temp Cable Tie, 8" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T18L0HSC2

**Type** T18L

**Color** Black (BK)

- Features and Benefits**
- Heat stabilized cable ties provide excellent resistance to high heat exposures.
  - Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** High Temp Cable Tie, 8" Long, 18lb Tensile Strength, PA66HS, Black, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 18.0 lbs

**Minimum Tensile Strength (Metric)** 80.0 N

**Length L (Imperial)** 8.0 "

**Length L (Metric)** 205.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.1 "

**Width W (Metric)** 2.5 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 2.17 "

**Bundle Diameter Max. (Metric)** 55.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 10000

## Material and Specifications

---

|                                      |  |
|--------------------------------------|--|
| <b>Material</b>                      | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>             | PA66HS                                 |
| <b>Flammability</b>                  | UL94 V2                                |
| <b>Halogenfree</b>                   | Yes                                    |
| <b>Operating Temperature</b>         | -40°F to +257°F (-40°C to +125°C)      |
| <b>ROHS Compliant</b>                | Yes                                    |
| <b>Certification/Specification</b>   | UL-ZODZ2.E64139                        |
| <b>UL Listed (US and Canada)</b>     | Yes                                    |
| <b>UL Recognized (US and Canada)</b> | Yes                                    |