

## T18MR0M4

Article Number: 113-00024

Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw, PA66, Black, 1000/pkg



Download spec sheet

### Base Data

<b>Local Order Number</b>	T18MR0M4
<b>Type</b>	T18MR
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mount design secures firmly on any #4 Screw</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul>
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Short Description</b>	Screw Mount Tie, 18lb 4.3" Long, Max Bun Diameter .79", #4 Screw, PA66, Black, 1000/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	18.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	80 N
<b>Length L (Imperial)</b>	4.3 "
<b>Length L (Metric)</b>	110.0 mm
<b>Fixation Method</b>	fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1 "
<b>Width W (Metric)</b>	2.5 mm
<b>Height H (Imperial)</b>	0.17 "
<b>Height H (Metric)</b>	4.2 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.8 "
<b>Bundle Diameter Max. (Metric)</b>	20.0 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.12 "
<b>Mounting Hole Diameter D (Metric)</b>	3.1 mm
<b>Thickness T (Imperial)</b>	0.039 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	3.1 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	3.1 mm
<b>Thickness T (Metric)</b>	1.0 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	1000
<b>Carton Quantity</b>	10000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes