

T18RA5000

Article Number: 120-05004

Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel



Download spec sheet

Base Data

Local Order Number	T18RA5000
Type	T18RA5000
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none">• The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.• Available in reels of 5,000 each or bandoliers of 50 each.
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Short Description	Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel

Product Dimensions

Minimum Tensile Strength (Imperial)	18.0 lbs
Minimum Tensile Strength (Metric)	80.0 N
Length L (Imperial)	4.0 "
Length L (Metric)	4.8 mm
Power Supply unit	Electrical
Tie Closure	plastic pawl
Width W (Imperial)	0.1 "
Width W (Metric)	2.5 mm
Bundle Diameter Min. (Imperial)	0.03 "
Bundle Diameter Min. (Metric)	0.7 mm
Bundle Diameter Max. (Imperial)	0.75 "
Bundle Diameter Max. (Metric)	20.0 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity (Metric)	5000
Carton Quantity	10000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MILSPEC	MS3367-4-9

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Certification/Specification SAE - AS33671
Cage Code 53421
UL-ZODZ2.E64139

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes