

T255R0HIRX2



Article Number: 111-25400

Heavy Duty Cable Tie, 20" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T255R0HIRX2

Type T255R

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 20" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1115.0 N

Length L (Imperial) 20.0 "

Length L (Metric) 508.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.6 mm

Bundle Diameter Min. (Imperial) 0.49 "

Bundle Diameter Min. (Metric) 12.5 mm

Bundle Diameter Max. (Imperial) 5.0 "

Bundle Diameter Max. (Metric) 127.0 mm

Thickness T (Imperial) 0.07 "

Thickness T (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 25 Pieces

Carton Quantity 500

Weight (Metric) 3.4 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes

Certification/Specification UL-ZODZ2.E64139

UL Listed (US and Canada) No

UL Recognized (US and Canada) No