

T30RA3000

Article Number: 103-00001

Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel



Download drawing



Download spec sheet

Base Data

Local Order Number	T30RA3000
Type	IT30RA
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs. • Available in reels of 3,000 each or bandoliers of 30 each.
Product Description	HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.
Short Description	Cable Tie for AT2060, 30 lb Tensile Strength, PA66, Natural, 3000/reel

Product Dimensions

Minimum Tensile Strength (Imperial)	30.0 lbs
Minimum Tensile Strength (Metric)	135.0 N
Length L (Imperial)	6.0 "
Length L (Metric)	152.0 mm
Cycle Time	1.2 seconds
Identification Plate Position	none
Reel Diameter (Imperial)	17.7 "
Reel Diameter (Metric)	450 mm
Reel Width (Imperial)	7.197 "
Reel Width (Metric)	182.8 m
Releasable Closure	No
Voltage Range	27 Volt
Width W (Imperial)	0.14 "
Width W (Metric)	3.6 mm
Bundle Diameter Min. (Imperial)	0.06 "
Bundle Diameter Min. (Metric)	1.5 mm
Bundle Diameter Max. (Imperial)	1.25 "
Bundle Diameter Max. (Metric)	31.0 mm
Thickness T (Imperial)	0.05 "
Power Supply	Electrical
Tension Force	Adjustable
Thickness T (Metric)	1.2 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	2
Package Quantity (Metric)	3000
Carton Quantity	6000
Reel Weight (Imperial)	7 lbs
Reel Weight (Metric)	3.175 kg
Weight (imperial)	3.9 lbs

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MILSPEC	MS3367-5-9
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Certification/Specification	UL-ZODZ2.E64139 Cage Code 53421 SAE - AS33671
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes