

## T30RSF9M4

Article Number: 126-00704

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 1,000/pkg



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T30RSF9M4

**Type** T30RSF(U)

**Color** Natural (NA)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
  - Push mount style creates low insertion and high extraction force.
  - Ties "clicks" into place upon final installation signaling installer insertion is complete.

**Product Description** Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

**Short Description** Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 1,000/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 30.0 lbs

**Minimum Tensile Strength (Metric)** 135 N

**Length L (Imperial)** 6.3 "

**Length L (Metric)** 161.0 mm

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.14 "

**Width W (Metric)** 3.6 mm

**Height H (Imperial)** 0.2 "

**Height H (Metric)** 5.7 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter Max. (Imperial)** 1.3 "

**Bundle Diameter Max. (Metric)** 31.0 mm

**Panel Thickness Max. (Imperial)** 0.09 "

**Panel Thickness Max. (Metric)** 2.4 mm

**Panel Thickness Min. (Imperial)** 0.04 "

**Panel Thickness Min. (Metric)** 0.9 mm

**Mounting Hole Diameter D (Imperial)** 0.19 - 0.22 "

**Mounting Hole Diameter D (Metric)** 4.7 - 5.5 mm

Mounting Hole Diameter D Min. 0.19 "  
(Imperial)

Mounting Hole Diameter D Max. 0.22 "  
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 5.6 mm  
(Metric)

Mounting Hole Diameter D Min. (Metric) 4.8 mm

Thickness T (Metric) 1.2 mm

## Logistics and Packaging

---

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

## Material and Specifications

---

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes