

T30XL9C2



Article Number: 111-02900

Standard Cable Tie, 14" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg



[Download spec sheet](#)

Base Data

Local Order Number T30XL9C2

Type T30XL

Color Natural (NA)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Standard Cable Tie, 14" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 14.0 "

Length L (Metric) 365.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14 "

Width W (Metric) 3.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 4.13 "

Bundle Diameter Max. (Metric) 105 mm

Thickness T (Imperial) 0.05 "

Cable Tie Head Length (Imperial) 0.24 "

Cable Tie Head Width (Imperial) 0.24 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 100 Pieces
Carton Quantity 5000
Weight (Metric) 1.8 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes
Certification/Specification UL-ZODZ2.E64139
UL Listed (US and Canada) Yes
UL Recognized (US and Canada) Yes