# HellermannTyton

#### **T50IDH9M4**



Article Number: 117-05303

Double Head Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg







#### **Base Data**

Local Order Number T50IDH9M4

Type T50IDH

Color Natural (NA)

Features and Benefits • The tie contains a dual locking design to secure two bundles at once.

· Head design can also provide spacing between parallel bundles.

· Bent tail allows for quick insertion into head.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head

also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent

and safe installation.

Short Description Double Head Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg

### **Product Dimensions**

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 12.0 "

Length L (Metric) 305.0 mm

Bundle Diameter 2nd Loop Max. 1.5"

(Imperial)

Fixation MethodNone

Identification Plate Position none

Number of Bundles 2

Releasable Closure No.

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.5 "

Bundle Diameter Max. (Metric) 38.0 mm

Bundle Diameter 1st Loop Max. 3.0 "

 $\begin{tabular}{ll} \textbf{(Imperial)} \\ \textbf{Bundle Diameter 1st Loop Max. (Metric)} \end{tabular} 76.2 \ \text{mm} \label{eq:max.pdf}$ 

Bundle Diameter 2nd Loop Max. 38.1 mm

(Metric)

# **Logistics and Packaging**

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 5000

# **Material and Specifications**

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Halogenfree Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes