

## T50MI0M4

Article Number: 113-00031

Screw Mount Tie, 50lb, 12.4" Long, Max Bundle Diameter 3.4", #10 Screw, PA66, Black, 1,000/pkg



Download spec sheet

### Base Data

<b>Local Order Number</b>	T50MI0M4
<b>Type</b>	T50MI
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Mount design secures firmly with any #10 screw.</li> <li>• Screw mount style creates low insertion and high extraction force.</li> </ul>
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Short Description</b>	Screw Mount Tie, 50lb, 12.4" Long, Max Bundle Diameter 3.4", #10 Screw, PA66, Black, 1,000/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	225 N
<b>Length L (Imperial)</b>	12.4 "
<b>Length L (Metric)</b>	315.0 mm
<b>Fixation Method</b>	fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19 "
<b>Width W (Metric)</b>	4.7 mm
<b>Height H (Imperial)</b>	0.23 "
<b>Height H (Metric)</b>	5.7 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	3.4 "
<b>Bundle Diameter Max. (Metric)</b>	85.0 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.22 "
<b>Mounting Hole Diameter D (Metric)</b>	5.5 mm
<b>Mounting Hole Diameter D Max. (Metric)</b>	5.5 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	5.5 mm

### Logistics and Packaging

Quantity Per bag

**Package Quantity (Metric)** 1000

**Carton Quantity** 5000

## **Material and Specifications**

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes