

## T50RTM25E8HM4

Article Number: 126-03504

Fir Tree Push Mount Ties, 8.3" Long, .25" - .28" Mounting Hole, PA66HIRHS, Grey, 1,000/pkg



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T50RTM25E8HM4

**Type** T50RTM25E

**Color** Gray (GY)

**Features and Benefits**

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

**Product Description** Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

**Short Description** Fir Tree Push Mount Ties, 8.3" Long, .25" - .28" Mounting Hole, PA66HIRHS, Grey, 1,000/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 222 N

**Length L (Imperial)** 8.0 "

**Length L (Metric)** 213.8 mm

**Fixation Method** Fir Tree

**Identification Plate Position** none

**Releasable Closure** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter Max. (Imperial)** 2.0 "

**Bundle Diameter Max. (Metric)** 50.8 mm

**Disc Diameter (Imperial)** 0.5 "

**Disc Diameter (Metric)** 12.6 mm

**Panel Thickness Max. (Imperial)** 0.5 "

**Panel Thickness Max. (Metric)** 13.9 mm

**Panel Thickness Min. (Imperial)** 0.09 "

**Panel Thickness Min. (Metric)** 2.3 mm

**Mounting Hole Diameter D (Imperial)** 0.28 "

**Mounting Hole Diameter D (Metric)** 7.0 mm

## Logistics and Packaging

---

**Quantity Per** bag  
**Package Quantity (Metric)** 1000  
**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
**Material Shortcut** PA66HIRHS  
**Flammability** UL94 HB  
**Operating Temperature** -40°F to +212°F (-40°C to +100°C)  
**ROHS Compliant** Yes