

## TAG11L-789

Article Number: 594-11789

Laser Tag Label, .65" X .20", 480 Per Sheet, Polyester, White, 5000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG11L-789

**Type** TAG11L

**Color** White (WH)

**Features and Benefits**

- LaserTags are sheet fed for easy loading and fast printing.
- LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
- LaserTags are printable using toner for long term UV exposure.
- LaserTags come in a variety of label sizes and types to fit most applications.

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Label, .65" X .20", 480 Per Sheet, Polyester, White, 5000/pkg

### Product Dimensions

**Length L (Imperial)** 0.20 "

**Length L (Metric)** 5.08 mm

**Width W (Imperial)** 0.65 "

**Width W (Metric)** 16.5 mm

**Height H (Imperial)** 0.20 "

**Height H (Metric)** 5.08 mm

**Height H2 (Imperial)** 0.2 "

**Height H2 (Metric)** 5.08 mm

**Height of printable area (imperial)** 0.20 "

**Height of printable area (metric)** 5.08 mm

**Horizontal Repeat HR (metric)** 19.05 mm

**Horizontal Repeat HR (imperial)** .750 "

**Print Method** Laser

**Thickness T (Metric)** 64.0 µm

**Vertical Repeat VR (metric)** 5.08 mm

**Vertical Repeat VR (imperial)** 0.2 "

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 5000

<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Labels per Column</b>	48
<b>Labels per Row</b>	10
<b>Labels per Sheet</b>	480

---

## Material and Specifications

---

<b>Material</b>	Type 789, Polyethylenterephthalat (PET)
<b>Material Shortcut</b>	789
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes