

TAG13L-789

Article Number: 594-13789

Laser Tag Label, .75" X .25", 312 Per Sheet, Polyester, White, 5000/pkg



Download spec sheet

Base Data

Local Order Number TAG13L-789

Type TAG13L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Color Marking Field White (WH)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Short Description Laser Tag Label, .75" X .25", 312 Per Sheet, Polyester, White, 5000/pkg

Product Dimensions

Length L (Imperial) 0.25 "

Length L (Metric) 6.35 mm

Width W (Imperial) 0.75 "

Width W (Metric) 19.05 mm

Height H (Imperial) 0.25 "

Height H (Metric) 6.35 mm

Height of printable area (imperial) 0.25 "

Height of printable area (metric) 6.35 mm

Horizontal Repeat HR (imperial) .963 "

Horizontal Repeat HR (metric) 24.30 mm

Print Method Laser

Thickness T (Metric) 64.0 µm

Vertical Repeat VR (metric) 6.35 mm

Vertical Repeat VR (imperial) 0.25 "

Width of Liner WL (metric) 215.00 mm

Width of Liner WL (imperial) 8.5 "

Logistics and Packaging

Quantity Per pack

Package Quantity 5000
Package Quantity (Metric) 5000
Carton Quantity 5000 Pieces
Labels per Column 39
Labels per Row 8
Labels per Sheet 312

Material and Specifications

Material Type 789, Polyethylenterephthalat (PET)
Material Shortcut 789
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)
Operating Temperature -40°F to +302°F (-40°C to +150°C)
ROHS Compliant Yes