

TAG15-600

Article Number: 595-15600

Dot Matrix Label, 1.0" X .50", 7 Across, Metalized Polyester, Silver, 5000/pkg



Download spec sheet

Base Data

Local Order Number TAG15-600

Type TAG15

Color Silver (SR)

Features and Benefits

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

Product Description Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

Short Description Dot Matrix Label, 1.0" X .50", 7 Across, Metalized Polyester, Silver, 5000/pkg

Product Dimensions

Length L (Imperial) 0.5 "

Length L (Metric) 12.7 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Height of printable area (metric) 12.70 mm

Horizontal Repeat HR (imperial) 1.100 "

Horizontal Repeat HR (metric) 27.94 mm

Print Method Dot-Matrix

Vertical Repeat VR (metric) 16.94 mm

Vertical Repeat VR (imperial) 0.667 "

Width of Liner WL (imperial) 8.6 "

Width of Liner WL (metric) 218.40 mm

Logistics and Packaging

Quantity Per pack

Package Quantity 5000

Package Quantity (Metric) 5000

Carton Quantity 1

Labels per Row 7

Weight (Metric) 0.11 kg

Material and Specifications

Material	Type 600, Polyester, silver-matt (SR)
Material Shortcut	600
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Halogenfree	No
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized