

TAG22T3-100B

Article Number: 596-00007

Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL



Download spec sheet

Base Data

Local Order Number TAG22T3-100B

Type TAG22T3

Color White (WH)

Features and Benefits

- HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.

Color Marking Field White (WH)

Product Description HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.

Short Description Thermal Transfer Self-Laminating Label, 1.0" X .5" X 1.43", 3 Across, Vinyl, White, 5000/RL

Product Dimensions

Length L (Imperial) 1.43 "

Length L (Metric) 36.3 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 1.43 "

Height H (Metric) 36.3 mm

Height H2 (Imperial) 1.43 "

Height H2 (Metric) 36.5 mm

Height of printable area (imperial) 0.5 "

Height of printable area (metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.137 "

Bundle Diameter Min. (Metric) 3.5 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.6 mm

Horizontal Repeat HR (metric) 27.3 mm

Horizontal Repeat HR (imperial) 1.075 "

Print Method Thermal Transfer

Thickness T (Metric)	25 µm
Vertical Repeat VR (metric)	41.28 mm
Vertical Repeat VR (imperial)	1.62 "
Width of Liner WL (imperial)	3.35 "
Width of Liner WL (metric)	85.09 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	5000
Package Quantity (Metric)	5000
Labels per Row	3

Material and Specifications

Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
Material Shortcut	100B
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized