

## TAG27-400

Article Number: 595-27400

Dot Matrix Label, 1.5" X .75", 4 Across, Metalized Polyester, Silver, 5000/pkg



Download spec sheet

### Base Data

Local Order Number TAG27-400

Type TAG27

Color White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

**Short Description** Dot Matrix Label, 1.5" X .75", 4 Across, Metalized Polyester, Silver, 5000/pkg

### Product Dimensions

Length L (Imperial) 0.75 "

Length L (Metric) 19.0 mm

Width W (Imperial) 1.5 "

Width W (Metric) 38.1 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.05 mm

Height of printable area (metric) 19.00 mm

Horizontal Repeat HR (imperial) 1.700 "

Horizontal Repeat HR (metric) 43.18 mm

Print Method Dot-Matrix

Vertical Repeat VR (metric) 25.40 mm

Vertical Repeat VR (imperial) 1.0 "

Width of Liner WL (metric) 193.70 mm

Width of Liner WL (imperial) 7.625 "

### Logistics and Packaging

Quantity Per pack

Package Quantity 5000

Package Quantity (Metric) 5000

Carton Quantity 5000

Labels per Row 4

Weight (Metric) 0.27 kg

## Material and Specifications

---

<b>Material</b>	Type 400, Polyester, white (WH)
<b>Material Shortcut</b>	400
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized