

Article Number: 594-49105

Laser Tag Self-Laminating Label, 1.0" X .35" X 1.0", 80 Per Sheet, Polyester, White, 2500/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG49L-105

**Type** TAG49L

**Color** White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Color Marking Field** White (WH)

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Self-Laminating Label, 1.0" X .35" X 1.0", 80 Per Sheet, Polyester, White, 2500/pkg

### Product Dimensions

**Length L (Imperial)** 1.0 "

**Length L (Metric)** 25.4 mm

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.4 mm

**Height H (Imperial)** 0.50 "

**Height H (Metric)** 12.7 mm

**Height H2 (Imperial)** 1.0 "

**Height H2 (Metric)** 25.4 mm

**Height of printable area (imperial)** 0.35 "

**Height of printable area (metric)** 8.89 mm

**Bundle Diameter Min. (Imperial)** 0.102 "

**Bundle Diameter Min. (Metric)** 2.60 mm

**Bundle Diameter Max. (Imperial)** 0.208 "

**Bundle Diameter Max. (Metric)** 5.30 mm

**Outside Diameter Min. (Imperial)** 0.102 "

**Outside Diameter Min. (Metric)** 2.6 mm

**Outside Diameter Max. (Imperial)** 0.208 "

**Outside Diameter Max. (Metric)** 5.30 mm

**Horizontal Repeat HR (imperial)** 1.000 "

**Horizontal Repeat HR (metric)** 25.40 mm  
**Print Method** Laser  
**Thickness T (Metric)** 35.0 µm  
**Vertical Repeat VR (imperial)** 1.0 "  
**Vertical Repeat VR (metric)** 25.40 mm  
**Width of Liner WL (metric)** 215.00 mm  
**Width of Liner WL (imperial)** 8.5 "

## Logistics and Packaging

---

**Quantity Per** pack  
**Package Quantity** 2500  
**Package Quantity (Metric)** 2500  
**Carton Quantity** 2500 Pieces  
**Labels per Column** 8  
**Labels per Row** 8  
**Labels per Sheet** 64

## Material and Specifications

---

**Material** Type 105, Polyester (PET), white (WH)  
**Material Shortcut** 105  
**Adhesive** Acrylic  
**Adhesive Shortcut** Acrylic  
**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)  
**Operating Temperature** -40°F to +300°F (-40°C to +149°C)  
**ROHS Compliant** Yes